

# BORN TO WORK

MF 1800 & MF 2800 E SERIES

34-57 HP

THE ECONOMICAL OVER ACHIEVERS



MASSEY FERGUSON

BORN TO **FARM**



# MF 1800 & MF 2800 E SERIES

EVERYTHING YOU NEED. NOTHING YOU DON'T.

Dependable, practical and hardworking sound like you? If you're looking for a compact 4WD tractor with those qualities, then you've come to the right place. The economical 1800 and 2800 E Series are practical get it done tractors, that reflect the soul of the famous Massey Ferguson dependability.



**Reliability is in the genes.** That's what you're really buying with a new 4WD Massey Ferguson compact tractor. The DNA of Massey Ferguson reliability. The capacity to work - and keep working, with our heavy cast rear end and front axle and robust rear three-point linkage.

The extra heft puts more power to ground, provides greater stability and supplies the muscle to knock out heavy-duty jobs that are typically handled by larger utility tractors.

**The dependability and fuel efficiency of Iseki engines.** Iseki engines are renowned for their quality of manufacture, reliability and frugal fuel consumption. The same engine found in a broad range of ag and construction equipment working in some of the harshest, most demanding conditions on earth. Now you can put them to work on your piece of paradise.

**Ask around and you'll hear our reputation.** And why it will pay to give Massey Ferguson a closer look. After all, we've been designing and building tractors since 1916.



#### 3-CYLINDER 1800E

1835E—34.5 engine (HP)

1840E—39.4 engine (HP)



#### 4-CYLINDER 2800E

2850E—48.8 engine (HP)

2860E—57.3 engine (HP)




# COMFORT, CONVENIENCE AND CONTROL

## BORN TO SIMPLIFY YOUR LIFE

Step up to the Massey Ferguson 1800 and 2800 E Series and enjoy the comfort of the spring-cushioned seat. Notice how all the controls are close at hand, easy to reach, simple to operate. Levers located to the right of the seat control the 3-point hitch. Controls for the lights and hand throttle are located on the steering column. And check out the visibility—to the ground and to the rear hitch. Now settle in and turn your “to-do” list to “done.”



► **Get the upper hand on loader work.** Work quickly, smoothly and easily.



► **Easy access to the fuel cap from ground level.** No long reaches over the hood or rear fender.



► **The standard folding ROPS** allows the MF 1800 and MF 2800 E Series ROPS to fit beneath a standard 7-foot garage door.





NEW ISEKI DIESEL ENGINES  
**DEPENDABLE,  
FUEL-EFFICIENT  
POWER**

## POWERFUL, CLEAN BURNING ENGINES

Within the E Series beats the heart of a work horse. A new brawny turbocharged 3-cylinder, 1.49 litre Iseki engine features in the MF 1800 E. While the larger-chassis MF 2800 E models get their powerful performance from a turbocharged 4-cylinder 2.43-litre power plant. These clean-burning engines are liquid cooled for durability, meet Final Tier IV emissions and offer generous torque to help you power through when the going gets tough.



# SIMPLE, SMOOTH HYDROSTATIC

Simple. Smooth. Easy-to-use. It gives you infinite speeds within each range so you can choose the most-efficient speed for any job. The hydrostatic transmission—which is controlled with the easy-to-use rocker pedal—offers the ultimate in ease and convenience. It's a great choice for loader work, mowing around objects—or any other chore requiring frequent change in direction.

## HYDROSTATIC TRANSMISSION FEATURES A ROCKER PEDAL CONTROL

Press your toe down to go forward, use your heel to move in reverse. Remove your foot from the pedal and the tractor stops. So intuitive, even the most inexperienced operator can master an E Series in no time at all.

**STRONG METAL HOOD AND FENDERS**  
add to the E Series backbone and durability.

**ALL SERVICE POINTS**  
are easy to access, making routine maintenance a breeze.



## BORN TO LOAD

Ready to work as hard as you do, the MF 1800 and 2800 E Series tractors offer a range of quick and easy attachments perfectly matched for pulling, shifting, or lifting tasks, ensuring maximum performance and efficiency. From standard or four-in-one front loaders, you have plenty of options to choose from. And with a fully integrated backhoe featuring heavy-duty construction, a cast iron bucket link, and a boom float that is typically found in construction-grade equipment, you can depend on its durability and reliability for all your digging and excavation needs.

## TECHNICAL SPECIFICATIONS

TRACTOR MODEL	MF 1835 E	MF 1840 E	MF 2850 E	MF 2860 E
Engine HP (kW) @ 2,600 rpm	34.5 (25.7)	39.4 (29.4)	48.8 (36.4)	57.3 (42.7)
PTO HP (kW) @ 540 rpm	27.6 (20.6)	31.5 (23.5)	38.5 (28.7)	45.3 (33.8)
Engine	Iseki, 1.83 L, 3-cyl diesel		Iseki, 2.43 L, 4-cyl diesel	
Aspiration	Turbocharged			
Emissions Control	Diesel Oxidation Catalyst (DOC), Exhaust Gas Recirculation (EGR), Diesel Particulate Filter (DPF)			
Hydrostatic Transmission	3-range HST, mechanically controlled, foot pedal on RH side			
Hydraulic System	Open centre, two gear-type pumps for steering and 3-point/remotes			
Steering Flow Lpm (gpm)	14.3 (3.8)		26.5 (7.0)	
Implement Flow Lpm (gpm)	28.9 (7.6)		47.8 (12.6)	
3-point Rear Hitch	Cat. I		Cat. I & II	
Lift Capacity – ball ends kg. (lbs.)	1,000 (2,205)		1,200 (2,645)	
Lift Capacity – 24 in. behind ball ends kg. (lbs.)	725 (1,598)		1,100 (2,425)	
PTO Type	HST: Transmission		Independent with SoftStart electronic modulation	
Overall Length mm (in.)	2,960 (116.5)		3,370 (132.8)	
Minimum Width mm (in.)	1,330 (52.4)		1,780 (70.1)	
Overall Height mm (in.)	2,480 (97.6)		2,635 (103.8)	
Ground Clearance mm (in.)	280 (11)		380 (15)	
Base Weight kg. (lbs.)	1,305 (2,877)		1,750 (3,858)	1,755 (3,869)
Fuel Tank L (gal.)	38 (10)		53 (14)	

TRACTOR MODEL	MF 1800 E	MF 2800 E
Loader Model	MF FL 2609	MF FL 2811
Tool Attachment Type	Euro Hitch	Euro Hitch
Maximum Lift Height – pivot pin (mm)	2600	2820
Maximum Lift Height – under level bucket (mm)	2400	2620
Lift Capacity to Maximum Height – pivot pin (kg.)	820	970
Lift Capacity to Max. Height – 500 mm. forward of pivot pin (kg.)	840	990
Lift Capacity to 1.5m. – pivot pin (kg.)	950	1140
Lift Capacity to 1.5m. – 500mm. forward of pivot pin (kg.)	950	1150
Breakout Force – pivot pin (kg.)	1240	1490
Breakout Force – 500mm. forward of pivot pin (kg.)	1110	1360
Maximum Dump Angle at Maximum height (degrees)	53°	48°
Maximum Rollback Angle at Maximum height (degrees)	42°	47°
Digging Depth (mm)	50	75
Weight (excluding bucket)	255	278

\*Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer or Distributor prior to any purchase.

► Customize your tyre selection by choosing the tread and size that best fit your job requirements and performance needs, including agricultural, industrial, and turf options.





[www.MasseyFerguson.com.au](http://www.MasseyFerguson.com.au)  
[www.MasseyFerguson.com.nz](http://www.MasseyFerguson.com.nz)

[www.facebook.com/masseyfergusonANZ](https://www.facebook.com/masseyfergusonANZ)  
[Twitter.com/MF\\_EAME](https://twitter.com/MF_EAME)  
[Instagram.com/MasseyFergusonGlobal](https://www.instagram.com/MasseyFergusonGlobal)  
[www.YouTube.com/MasseyFergusonGlobal](https://www.YouTube.com/MasseyFergusonGlobal)



MASSEY FERGUSON® is a worldwide brand of AGCO.  
© AGCO Corporation



MASSEY FERGUSON

BORN TO **FARM**