

RX6030 SP / RX8030 SP

KIOTI UTILITY TRACTOR




KIOTI

Specifications

MODEL		RX6030 SP	RX8030 SP
ENGINE			
Make		Kioti	Daedong
Model		4B243DTM-A	4F243DTM-A
Type		4Cyl., Turbo Charge Diesel Engine	4Cyl., Turbo Charge Diesel Engine
Engine Gross Power	HP	60	76
No, of Cylinders		4	4
Displacement	cc	2,435	2,435
Rated Revolution	rpm	2,600	2,600
Fuel Tank Capacity	ltr	85	85
Engine Oil	ltr	7	8.3
PTO			
Rated PTO Power	HP	52.3(39)	65.5(49)
Rear PTO Type		Independent	Independent
Rear PTO Speed	rpm	540	540
DRIVE TRAIN			
Transmission		Synchro Shuttle Transmission	Synchro Shuttle Transmission
Speeds		12F x 12R	12F x 12R
Differential Lock		Rear Standard	Rear Standard
Steering		Hydrostatic Power Steering	Hydrostatic Power Steering
Main Clutch Type		Dry Single Plate Clutch	Dry Single Plate Clutch
Brake		Wet Multi Disc	Wet Multi Disc
Front Wheel Drive System		Hydro Multi Wet Disc Clutch	Hydro Multi Wet Disc Clutch
HYDRAULIC SYSTEM			
3 Point Lift Control Type		Position, Draft, Mixed Control	Position, Draft, Mixed Control
Implement Pump	lpm	41.6	41.6
Power Steering Pump	lpm	26	31.2
Total Hydraulic Flow	lpm	67.6	72.8
3 Point Hitch Type		Category II	Category II
Lift Capacity at 610 Behind		1,630	1,768
Drawbar Type		Drawbar	Drawbar
No. of Standard Remote Valves (Rear)		(- / 1)	(- / 1)
TIRE SIZE			
Industrial		Low Lug	Low Lug
Front		11.2 - 20	11.2 - 24
Rear		14.9 - 30	16.9 - 30
TRAVELING SPEEDS			
Forward	km/h	1.51 ~ 35.07	1.51 ~ 35.07
Reverse	km/h	1.49 ~ 34.48	1.49 ~ 34.48
OTHERS			
Tilt Steering		Std	Std
One-Touch Hood Type		Std	Std
Panel Type		Electric	Electric
DIMENSIONS			
Overall Length (W/O Front Weight and 3Pt Hitch)	mm	3,410	3,480
Overall Width (Minimum Tread)	mm	1,800	1,960
Tread Width - Front	mm	1,465	1,475
Tread Width - Rear	mm	1,415	1,515
Overall Height (ROPS)	mm	2,700	2,730
Wheel Base	mm	2,100	2,130
Ground Clearance	mm	420	440
Turning Radius (W/O Brake)	mm	3,640	3,930
Turning Radius (with Brake)	mm	3,110	3,370
Weight (with ROPS)	kg.f	2,360	2,535

*NOTE : Specifications and design are subject to change without notice

Standard Equipment

- Rear Remote Hydraulic Valve
- Rear PTO
- Draft Control
- 4WD
- Auto 4WD
- Rear View Mirror
- Parking Brake
- Battery
- Horn
- 7 Pin Socket
- Rear Work Light
- Signal Lamp
- PTO Cover
- ROPS
- Suspension Type Deluxe Seat
- Cup Holder



HIGH PROJECTION HEAD AND WORKING LAMP

With the new projection head and working lamp, the operator will experience safe and easier operation in the dark operating conditions.



HYDRAULIC 4WD

The 4WD is engaged with just simple push of switch.



TRANSMISSION

The new SynchroShuttle on the RX Series provides smooth and easy shifting from forward to reverse.

The transmission features 12 forward and 12 reverse gears to handle all kinds of jobs.



PFG Australia
199 Australis Drive, Derrimut VIC 3030 Australia
T: 03 8353 3600
F: 03 8353 3699
www.kiotitractors.com.au



ISO 9001
NO.954596



ISO 14001
NO.771475



OHSAS 18001
NO:K033008



OHSAS 18001
NO:K033008



World class
300Award