

PREMIUM SERIES

Widespread Spreader Spread to 36m







PREMIUM SERIES





Widespread 12 Tonne Spreader - Spread to 36m

The broadacre range of VRT Spreaders come in the largest size for maximum spread-ability. Combining the versatility of a Gason spreader with the latest innovations in technology, the VRT range will cover any of your spreading requirements.

You'll be spreading with ease with an abundance of optional extras such as load cells, tail light kit, braked axles and tarp kit.

Two supplied sets of Spinners and removable Centre Vee make these premium spreaders easily interchangeable from general purpose to granular fertiliser.

Whilst Ground Drive comes with a bin mounted tacho as standard, the Premium Series also offer a range of VRT control options for those wanting a greater level of functionality.

Widespread Spreader Specifications				
Dimensions (mm)	12T			
Overall width (2m centres)	2850			
Overall width (3m centres)	3750			
Bin width	2355			
Overall height*	2920			
Side of bin height	2780			
Overall length**	6780			
Bin length	4000			
Standard wheel centres (2m)	2080			
Row Crop wheel centres (2m)	2000			
Standard wheel centres (3m)	2980			
Row Crop wheel centres (3m)	3000			
Front step height	540			
Ground clearance	520			
Spinner height to ground	1000			

*Heights measured with 450mm under front hitch and no tarp kit.

**Add 195mm to overall length if load cells kit is fitted

Maximise your capabilities with the largest of the Gason spreader range. Contractors and broadacre farmers will love the sheer capacity of these solid machines!

12 TONNE OPTIONS & EXTRAS

- VRT Monitor Options SmartAg, Topcon, John Deere available
- Tarp Kit with long handle for ease of use
- Calibration Kit to determine accuracy of pelletised products
- Load Cell Kit calculate your application rate accurately
- Heavy Duty Spinners for heavy materials
- · Independent Feed Chain / Spinner Hydraulic Kit
- · Taillight & Beacon Light Kits
- · Wheel chocks & Holder
- 3m axle or 2.2m-3m multiset axle option (2m axle standard)

Widespread Spreader Specifications						
Spreader Weight (kg)						
Unloaded	3000					
Max. Loaded weight (gross) @ 25 km/h	15830					
Bin Capacity By Volume (L)						
Bin Shape	10690					
Bin Capacity By Weight (kg)						
Urea (estimated)	8010					
Super (estimated) (urea @ 750kg / 1000L) (single super @ 1200kg / 1000L)	12830					
Spinners						
General Purpose	Standard					
Widespread	Standard					
Heavy Duty (manure)	Optional					
Flotation Tyres (Size)						
Standard Tyres	750/60-30.5					
Row Crop Tyres (optional)	480/80 R34					



Notes:			